## Unit OOAL Jib Reefing & Furling

Unit 00AL is the perfect jib reefing and furling system for small cruising boats under 26 ft (8 m). It combines most of the features of larger Harken® furling systems in a simpler unit. Like other Harken® systems, the main components of the 00AL are 6061-T6 Hardkote-anodized aluminum with Teflon® impregnation.

Features include a free-spinning, omnidirectional bearing system with multiple ball bearing races, a double grooved foil for racing sail changes, and a light-weight halyard swivel to minimize windage and weight aloft. The furler's large inside spool provides plenty of mechanical advantage for smooth, easy reefing and furling.

There are enough aluminum foil sections to build a headstay with a pin-to-pin measurement to 31 ft 6 in (9.60 m). Harken® offers an additional foil and connector to extend headstay length to 35 ft (10.7 m).

Note: You must cut your headstay to install 00AL furling. You must also purchase a Harken® clevis pin to match your chainplate.













Bearing shields protect Air Swivel® and tack bearings from UV and dirt

Small Air Swivels® turn freely on computer-designed bearing races to reduce windage and weight aloft

Large-diameter ball bearings minimize friction, require no lubrication or isolating seals

Pressure-cast sculpted aluminum line guard is open for easy line access



Typical Boat Length 20' - 26' (6 - 8 m)

		iypicai bual Ediiylii 20 - 20 (0 - 0 iii)		
Wire Ø	(1 x 19 SS)	Rod Ø	Clevis Pin Ø	
1/8", 5/32", 3/	6" (3, 4, 5 mm) -4 (	4.37 mm)	1/4", 5/16", 3/8", 7/16" (6, 8, 9.5, 11 mm)	
<b>Headstay Length</b>	Standard 9.60 m (31'6"); max 10.67	m (35')		
Part No.	Description			
1110	Furling system			
Clevis Pin Asser	nbly Required - sold separately			
1106	¹/₄" (6 mm)			
1107	5/16" (8 mm)		,	
1108	³/ <sub>8</sub> " (9.5 mm)		, and the second	
1109	<sup>7</sup> / <sub>16</sub> " (11 mm)			
Optional Parts				
909	Extra 6" (152 mm) connector			
1112	Extra 3.5' (1.07 m) foil extrusion			
7404	Lead block kit: 3 x 7403/1 x 7402/1	x 7401/1 cleat	,	
884	Snap shackle for tack/head (each sh	nackle)		
061	Stanchion mount base			
944	Halyard restrainer (use only when re	equired)	·	

Consult with Harken® if boat length exceeds specifications above

