

MKIV Unit 2 Typical Boat Length 35' - 46' (10.6 - 14.2 m)

Wire Ø (1 x 19 SS)	Rod Ø	Clevis Pin Ø
5/16", 3/8" (8, 10 mm)	-12, -17, -22 (7.14, 8.38, 9.53 mm)	5/8", 3/4" (15.9, 19.1 mm)

Headstay Length Standard 60'4" (18.38 m); max 67'4" (20.51 m)

Part No.	Description
7412.10	Furling system

Toggle Assembly Required - sold separately

7412.20 5/8	Eye/Jaw reversible toggle assembly with 5/8" (15.9 mm) clevis pin
7312.20 5/8	Jaw/Jaw toggle assembly with 5/8" (15.9 mm) clevis pin
7312.20 3/4	Stud/Jaw toggle assembly with 3/4" (19.1 mm) clevis pin
7312.21 5/8	Long link plate with toggle with 5/8" (15.9 mm) clevis pin
7312.21 3/4	Long link plate with toggle with 3/4" (19.1 mm) clevis pin

Optional Parts

7412.30	Extra 7' (2.13 m) luff foil extrusion
7412.31	Extra 9" (229 mm) connector with bushings
7424 -12	-12 Rod adaptor stud (thread Ø UNF 5/8")*
7425 -17	-17 Rod adaptor stud (thread Ø UNF 5/8")*
7426 -22	-22 Rod adaptor stud (thread Ø UNF 3/4")*

*Use with conventional turnbuckle

NEW

MKIV Unit 3 Typical Boat Length 45' - 60' (13.7 - 18.3 m)

Wire Ø (1 x 19 SS)	Rod Ø	Clevis Pin Ø
7/16", 1/2" (11, 12 mm)	-22, -30 (9.53, 11.10 mm)	3/4", 7/8" (19.1, 22.2 mm)

Headstay Length Standard 75'1" (22.88 m); max 82'1" (25.02 m)

Part No.	Description
7413.10	Furling system*

Toggle Assembly Required - sold separately

7413.20 3/4	Jaw/Jaw with short link plate with 3/4" (19.1 mm) clevis pin
7413.20 7/8	Jaw/Jaw with short link plate with 7/8" (22.2 mm) clevis pin
7313.21 3/4	Long link plate with toggle with 3/4" (19.1 mm) clevis pin
7313.21 7/8	Long link plate with toggle with 7/8" (22.2 mm) clevis pin

Optional Parts

7413.30	Extra 7' (2.13 m) luff foil extrusion
7413.31	Extra 9 3/4" (248 mm) connector with bushings
7426 -22	-22 Rod adaptor stud (thread Ø UNF 3/4")**
7427 -30	-30 Rod adaptor stud (thread Ø UNF 7/8")**

Available January 2009 *Line not included **Use with conventional turnbuckle

NEW

MKIV Unit 4 Typical Boat Length 65' - 80' (19.8 - 24.4 m)

Wire Ø (1 x 19 SS)	Rod Ø	Clevis Pin Ø
1/2", 9/16", 5/8" (12, 14, 16 mm)*	-30, -40, -48 (11.10, 12.7, 14.3 mm)	7/8", 1", 1 1/8" (22.2, 25.4, 28.57 mm)

Headstay Length Standard 75'1" (22.88 m); max 89'1" (27.15 m)

Part No.	Description
7414.10	Furling system**

Toggle Assembly Required - sold separately

7414.20 7/8	Jaw/Jaw with short link plate with 7/8" (22.2 mm) clevis pin
7414.20 1	Jaw/Jaw with short link plate with 1" (25.4 mm) clevis pin
7414.20 1 1/8	Jaw/Jaw with short link plate with 1 1/8" (28.57 mm) clevis pin

Optional Parts

7414.30	Extra 7' (2.13 m) luff foil extrusion
7414.31	Extra 10 3/4" (270 mm) connector
7427 -30	-30 Rod adaptor stud***
7428 -40	-40 Rod adaptor stud***
7429 -48	-48 Rod adaptor stud***

Available January 2009 *For 3/4" (19 mm) wire Ø contact Harken **Line not included

***Use with conventional turnbuckle

7412.30
7413.30
7414.30



7412.31
7413.31
7414.31

7424 -12
7425 -17
7426 -22
7427 -30
7428 -40
7429 -48

7412.20 5/8

7312.20 5/8

7312.20 3/4

7413.20 3/4
7413.20 7/8
7414.20 7/8
7414.20 1
7414.20 1 1/8



7312.21 5/8
7312.21 3/4
7313.21 3/4
7313.21 7/8